



Table rifle scope – Rusan adapter size

JVS GLOBAL OUTDOOR
ALLES VOOR DE BUITENSPORTER

We are not responsible for the accuracy of the data, sizes are taken from scope manufacturers catalogue.

Contents

AKAH.....	1
BAUER.....	1
BLASER.....	2
BURRIS.....	2-3
DDOPTICS.....	3
DEDAL NV.....	3
DELTA OPTICAL.....	4-5
DOCTER.....	5
GPO.....	6-7
HAWKE.....	7-8
IOR.....	8-9
KAHLES.....	9-11
KITE OPTICS.....	11
LEICA.....	12-13
LEUPOLD.....	13
MEOPTA.....	13-14
MINOX.....	15
NIGHTFORCE.....	16
NOBLEX.....	16-17
PROFESSOR OPTIKEN.....	17-18

SCHMIDT BENDER	18-19
SIGHTMARK	19-20
STEINER.....	20
SWAROVSKI.....	21-22
VORTEX.....	22-24
VIXEN.....	24
ZEISS	25-27
YUKON.....	27

NOTES for adapter sizes with */ - (ARM52-30ZM* - for scopes ...x24 with ZM rail, ARM52-56.7** and ARM52-62.7**)**

- *ARM52-30ZM-1 ... Rusan Q-R adapter for devices with thread M52x0.75 - for Zeiss Conquest V6 1.1-6x24 with rail
- *ARM52-30ZM-2 ... Rusan Q-R adapter for devices with thread M52x0.75 - for Zeiss Diavari-ZM 1,25-4x24 / Varipoint VM 1,1-4x24 with rail
- *ARM52-30ZM-3 ... Rusan Q-R adapter for devices with thread M52x0.75 - for Leica Magnus 1-6,3x24i / Fortis 6 1-6x24i with rail
- *ARM52-30ZM-4 ... Rusan Q-R adapter for devices with thread M52x0.75 - for Zeiss Victory V8 1.1-8x24 with rail
- ** ARM52-56.7** and ARM52-62.7** ... short adapters for ZEISS VICTORY DIARANGE with laser rangefinder

Some facts about Rusan adapter clamps

- Adapter clamp can be **adjusted** for **ONLY +/- 0,2** mm from the nominal diameter
- It is always important for us to know the **exact information** about the **outside diameter (NOT lens diameter)** of the riflescope
- Clamping lever is supposed to be opened and closed with one finger (1,4 - 1,6 Nm on main adapter screw)
- For MAR-FX clamps (with 3 screws) recommended torque is 1,2 Nm
- If there in the table is no appropriate dimension, other sizes on inquiry

